

## TECHNICAL SPECIFICATION

### LEISURE 4.0

CHARACTERISTIC	STANDARD	UNIT	RESULT
Surface treatment			PUR (UV Curved)
Format			Sheet
Roll Length		m	16
Width	EN 426	mm	1,800
Thickness	EN 428	mm	4.0
Weight	EN 430	g/m <sup>2</sup>	2,680
Dimensional Stability	EN 434		Fullfilled < 0.2
Slip Resistance	DIN51130		R9
	EN 13893		DS
Wear Resistance	EN 660-2	group	T
Chemical Resistance	EN 423		good
Flexibility	EN 434		No Crack
Impact Sound Insulation	ISO 10140	dB	18
Reaction to Fire	EN 13501-1		Cfl-s1
Thermal Resistance	EN 12664		suitable for underfloor heating
Friction	NF EN 13036-4		Average 105
Vertical Deformation	EN 14809	mm	0.4
Vetical Ball Rebound	NF EN 12235	%	Average 99
Behavior Under A Rolling Load	NF EN 1569		No Damage
Resistance of Wear	EN ISO 5470-1	g	0.16
Resistance to Static Load	NF EN 1516	mm	Fullfilled < 0.2
Resistance to Impact	NF EN 1517		No Damage

